

AH7010

VIDEO CONFERENCE CAMERA



View Angle
3.3° (Tele)-60°(Wide)



Optical Zoom
12X








Digital Zoom
16X

Technical Specifications

Full HD, Wide View Angle, Multi-protocols, Multiple Video Interfaces.
The AH7010 series camera offers perfect functions, superior performance and rich interfaces. The features include advanced ISP processing algorithms to provide vivid images with a strong sense of depth, high resolution, and fantastic colour rendition. It supports H.264/H.265 encoding which makes motion video fluent and clear even under less than ideal bandwidth conditions.

Model - AH 7010			
View Angle	3.3° (Tele)-60° (Wide)	Iris/Electronic Shutter	Auto/Manual
Iris	F 1.6-F 3.5, f=5.5~110mm	Focus	Auto/Manual
sensor	1/2.8 inch high quality HD CMOS sensor	BLC	ON/OFF
Effective Pixels	2.07MP, 16: 9	WDR	OFF/ Dynamic level adjustment
Optical Zoom	12X	Video Adjustment	Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve
Digital Zoom	16X	SNR	>55dB
Minimum Illumination	0.5Lux (F1 (F1.8, AGC ON)		
DNR	2D&3D DNR		
White Balance	Auto/ Manual/ One Push/ 3000K/3500K/4000K/4500K/ 5000K/5500K/6000K/6500K/7K		
Video Interfaces	1x USB 2.0, 1x LAN, 1 x RS232	Video Format	USB2.0 interface video format 176x144/320x240/320x1801 352x288/640x480/720x480/720x5761640x360800X600/ 960X540/1024X57611024X76811280X 7201 1920X1080P30/25/20115/10/5
Video Compression Format	H.264, H.265, Dual stream Output		USB3.0: 1920X1080P60/50/30/25, 1280X720P30/25115110, 960X540P30, 640X360P30,800X600P30
Control Protocol	VISCA/Pelco-D/Pelco-P		
Resolution	Baud Rate 115200/9600/4800/2400bps Full HD		
Audio compression Format	AAC/MP3 Audio		
LAN Port	100M IP port (100BASE-TX), Support VISCA protocol control through IP port		
Network Protocol	RTSP, RTMP, ONVIF, GB/T28181		
Power Interface	HEC3800 outlet (DC12V)		
Pan/Tilt Rotation	±170°, -30° +90°	Power Adapter	ACI 10V-AC220V to DC12V/1.5A
Pan Control Speed	0.1 ~60°/sec	Dimension	150mmX150mmX167.5mm
Tilt Control Speed	0.1~30°/sec	Weight	1.4KG
Preset Speed	Pan: 60°/sec, Tilt 30°/sec	Remote Operation (IP)	Remote Upgrade Reboot and Reset
Preset Number	255 presets (10 presets by remote controller)		

Dimension(mm):



AVAILABLE THROUGH PAN INDIA DISTRIBUTOR & DEALER NETWORK



www.atdscindia.com