



CFM100 & DFM100

FLUSH MOUNT DIGITAL CONFERENCE SYSTEM WITH CAMERA TRACKING



The Flush Mount Digital Audio Conference System with Speaker Tracking provides seamless connectivity with an intelligent central control system and video conferencing solution for modern conference applications.

FEATURES

- Aluminum panel finish with embedded flush mount installation.
- Lockable side clamps for firm and secure table mounting.
- 2.1 Meter CAT6 network cable with microphone interface.
- Twin RJ45 ports with 2 Meter cable for Loop In – Loop Out (Daisy Chain) connection.
- Built-in Hi-Fi condenser microphone capsule for high articulation and low noise reproduction.
- Advanced anti-feedback and voice pickup technology.
- Anti-interference circuit design to reduce mobile phone interference.
- LED ring indicator on microphone glows during operation.
- Shotgun type gooseneck microphone with 4-pin female connector and flexible stem for convenient angle adjustment.
- Chairman unit comes with touch-sensitive backlit priority and On/Off buttons.
- Multiple chairman units can be connected at any position in the system.

TECHNICAL SPECIFICATIONS

Specification	Chairman Unit	Delegate Unit
Model No.	CFM100	DFM100
Touch Sensitive Backlit Buttons	Yes	Yes
Priority Button	1	-
On/Off Button	1	1
Microphone Interface Cable	2.1 Meter CAT6 Cable	
Working Voltage	DC 24V	
Daisy Chain Connector	Twin CAT6 Port Connector with 2 Meter Cable	
Capsule Type	Super Cardioid	
Sensitivity	-46 dBV/Pa ±2dB @1KHz	
Frequency Response	20Hz – 20KHz	
Input Impedance	1 kΩ	
Directional	0°/180° >20dB (1KHz)	
Equivalent Noise	20 dBA (SPL)	
SPL	125 dB (THD <3%)	
S/N Ratio	>68dB	
Cross Talk	>80dB	
T.H.D	<0.05%	
Microphone	Shotgun Gooseneck with 4-Pin Female Connector	
Dimensions	Base: 140mm x 50mm x 100mm Microphone Length: 360mm	
Colour	Black	
Installation	Flush Mount with Side Locks	

AVAILABLE THROUGH PAN INDIA DISTRIBUTOR & DEALER NETWORK

